

6 and 10 Port Industrial Giga Managed Switches, Model IESMG 30X-2S A



IESMG 6 and 10 Port series Industrial L2 Managed Switch adopt Store-and-Forward architecture, fan-less and energy-saving design to provide reliable and stable operation in harsh industrial environments.

All the switches support 12-58VDC dual power input and operate at temperature of -40 to 85°C.

While using standard Cat5 / 5e / 6 cables that carry Ethernet data, the switch can also provide power to a Powered Devices, such as VoIP phones, video cameras, wireless access points, alarms, traffic controllers, sensors and tracking devices.

Features

- ERPS (G.8032) Ring Technology
- Loop Protection
- SFP fiber port support 1.25G / 155M
- 9.6K Jumbo Frame
- 12-58V DC Dual power input with polarity reverse protection
- 6KV Surge protection for Power and copper port
- 8-15KV ESD protection
- IP40 enclosure
- Din-rail installation, Wall-mounted optional
- Low power consumption, lead-free process

Specification

Model	10 Port, 8Copper 2 SFP	6 Port, 4Copper 2 SFP
Performance		
Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.1Q, IEEE802.1w, IEEE802.1s, IEEE802.1d, IEEE802.1ag	
Processing type	Store and Forward / Cut through or fragment free switching	
Protocols	TCP, UDP, ARP, ICMP, ICMP Router Discovery	
Switch Capacity	55Gbps Non-blocking	
Packet forwarding Rate	14.88Mpps	8.93Mpps
MAC address	8k	
Buffer Space	4M	
Jumbo Frame	9.6k	
Interface		
Copper port	10 / 100 / 1000M Auto-negotiation, RJ45 Auto-Cross for MDI/MDIX Cat5 / Cat5e / Cat6, ≤100m	
Fiber	2*100 / 1000Base-X SFP Slot. TX Power & RX Sensitivity based on SFP Modules	
Console	RS232 (RJ45)	
Reset	Key switch	

San Telequip (P) Ltd.,
 504 & 505 Deron Heights, Baner Road
 Pune 411045, India
 Phone : +91-20-27293455, 9764027070, 8390069393
 email : info@santelequip.com



LED indicators	PWR, RUN, Speed, Link / Act, PoE	
Relay	Normal Open	
Power		
Input Voltage	12 to 58VDC Dual Redundant 6-PIN Removable Terminal Block Overload Voltage protection Overload Current protection Reverse Polarity protection	
Power Port	Terminal Block	
Input Current	Max 0.35A @ 24V DC	Max 0.25A @24V DC
Power Consumption	8.5W	6W
Physical characteristics		
Dimension	138x107x56mm	
Enclosure	IP40 , Aluminum Alloy, Fan-less	
Installation	DIN-rail, Wall-mounted	
Weight	540g	
Environment		
Working Temperature	-40℃ to +85℃	
Storage Temperature	-40℃ to +85℃	
Relative Humidity	5-95% (no condensation)	

Software Features

L2 Feature	
Port Features	IEEE 802.3x Flow control
	Interface counters
	Broadcast Storm control
	Isolated Port
	Port Mirroring
Link Aggregation	Static Aggregation
	IEEE802.1q
	Dynamic Aggregation, LACP
MAC-address table	Static MAC-address
	Dynamic MAC-address
	Security MAC-address
	IVL mode
Mirror	Port-based Mirror
	VLAN-Based
	Flow-Based
Spanning Tree	IEEE802.1d STP
	IEEE802.1w RSTP
	IEEE802.1s MSTP

San Telequip (P) Ltd.,
 504 & 505 Deron Heights, Baner Road
 Pune 411045, India
 Phone : +91-20-27293455, 9764027070, 8390069393
 email : info@santelequip.com



GVRP	Supported
Q in Q	VLAN-based Q In Q
	1:1 VLAN Mapping
LLDP	LLDP
	LLDP-MED
Loop Protection	Support
ERPS (G.8032)	Single Ring, Sub-Ring, Multi-Ring
	Load balance
	Recovery Time < 50ms
BPDU Filtering	Per Port
Host ARP table	Yes
VLAN	4094 VLAN
	Port-based VLAN
	GVRP
Protocol VLAN	MAC-based VLAN
	Protocol-based VLAN
	IP Subnet-based VLAN
Voice VLAN	Static entry
	LLDP-MED
Private VLAN	Support
Port Isolate	Support
IGMP Snooping	IGMP V1 Snooping
	IGMP V2 Snooping
	IGMP V3 Snooping
	Source Port Check
	IGMP Fast Leave
	IGMP Filter
	IGMP Proxy
MLD Snooping	MLD V1 Snooping
	MLD V2 Snooping
	Source Port Check
	MLD Fast Leave
	MLD Filter
MVR	MLD Proxy
	Static mode
	Dynamic mode
	Fast Leave

Security

ACL	ACL (IP Standard ACL), IPv4 / IPv6
	MAC extend ACL
	IP extend ACL
	L2, L3, L4 fields match
	Log, Redirection, Mirroring, Speed limit
Additional Features	IP Binding per Port, Port trunking Static IEEE 802.1p QoS / CoS / ToS / DSCP priority queuing Port Mirroring, Auto sensing, Dynamic ARP Inspection ARP Snooping / Spoofing prevention, Loopback detection / STP Loopback detection, Priority Mapping, DiffServ Marking BootDoS attack prevention, DHCP Server Screening, Head of Line(HoL), BootP, Digital Diagnostic Monitoring Interface (DDMI) support IEEE 802.1x Port Access Authentication, User authentication for Web GUI, Ingress policing, Auto QoS
Access Control list (ACL)	Port based, VLAN based, Bidirectional ACL
QoS	QoS Class, Remarking
	SP, WRR queue scheduling
	Ingress port-based rate-limit
	Ingress priority-based rate-limit
	Egress port-based rate-limit
	Egress queue-based rate-limit
	Policy-based QoS
	Storm Control
	8 queues per port
Dot1x	Port Access Control
	User Access Control
	MAC-address Access Control
	RADIUS Server
	TACACS+ Server
IP Source Guard	Dynamic entry (from DHCP Snooping)
	Static entry
ARP Inspection	Dynamic entry (from DHCP Snooping)
	Static entry
Port Security	Support
Access Management	Support

San Telequip (P) Ltd.,
 504 & 505 Deron Heights, Baner Road
 Pune 411045, India
 Phone : +91-20-27293455, 9764027070, 8390069393
 email : info@santelequip.com



Management

User management	Password protection
SNMP	SNMP V1 / V2c / V3 (MIB)
SNTP	Yes
	System configure, Restore and Backup
RMON	Statistics Group
	History Group
	Alarm Group
	Events Group
Web management	WebUI with HTTP V1.1, HTTPS
Other	SmartPort, Syslog, DHCP Server
Firmware Upgrade	Reversion Upgrade
IPv4/IPv6	Support
CLI	Support
RADIUS client	Support
Syslog / Debug	Support
Diagnosis	Ping (IPv4), Ping (IPv6)
	Trace route (IPv4),
	Trace route (IPv6)

Application

NTP	NTP Client
DHCP	DHCPv4 Client, DHCPv6 Client
DHCP Snooping	DHCP snooping table
	Trust Port
Telnet	Telnet Server
TFTP	TFTP Client
SSH	SSH Server

San Telequip (P) Ltd.,
 504 & 505 Deron Heights, Baner Road
 Pune 411045, India
 Phone : +91-20-27293455, 9764027070, 8390069393
 email : info@santelequip.com



Approvals & Standards Tested for

Electro Magnetic Interference EMISSIONS : EN55032 : 2015

- | | | |
|---|------------------------|---|
| 1 | EN55022 / 55032 : 2015 | Conducted Disturbance, Radiated Disturbance |
| 2 | IEC 61000-3-2 : 2014 | Harmonic Current Emissions |
| 3 | IEC 61000-3-3 : 2013 | Voltage Fluctuation & Flicker |

Electro Magnetic Immunity / Susceptibility : EN55024 / EN55035 : 2017

- | | | |
|---|----------------------|--|
| 1 | IEC 61000-4-2 : 2009 | Electrostatic Discharge |
| 2 | IEC 61000-4-3 | RF Immunity |
| | | Continuous Radiated Disturbance |
| 3 | IEC 61000-4-4 | Electrical Fast Transient |
| 4 | IEC 61000-4-5 | Surge Immunity |
| 5 | IEC 61000-4-6 | Conducted RF immunity |
| | | Continuous Conducted Disturbance |
| 6 | IEC 61000-4-8 | Power Frequency Magnetic Field |
| 8 | IEC 61000-4-11 | AC Voltage Dips & Interruption/Variation |

SAFETY : EN 62368 / EN 60950

FCC : FCC 47 CFR Part 15B 15.107(a), 15.109(a)

Order Information : IESMG 30X-2S A

IESMG : Industrial Grade Giga Managed Ethernet Switch
 30X : X is 4 or 8 of 10 / 100 / 1000 Copper Port
 2S : 2 of 100 / 1000 SFP Ports
 A : Fixed

Note : SFP to be purchased separately

Ordering Code Example

Model	Description
IESMG 304-2S A	10 / 100 / 1000M 4-RJ45, 2-SFP
IESMG 308-2S A	10 / 100 / 1000M 8-RJ45, 2-SFP